



Loveshaw

Uniform Legend

Case Sealing for the Real World

This reliable case sealer for industrial environments seals a wide range of uniform cases.

Little David delivers packaging equipment that works for you



Interchangeable top and bottom cartridges



The Legend offers:

- ☑ Low maintenance
- ☑ Safe CE listed
- ☑ Quick changeover
- ☑ Simple operation
- ☑ Interchangeable tape cartridges
- ☑ Heavy duty
- ☑ Reliable

The Legend replaces:

- ☑ Expensive labour
- ☑ Hand taping boxes
- ☑ Unsafe machinery

Little David Uniform Legend



Uniform Legend



LEGEND Case Sealing Uniform

Uniform case sealing machines are designed for use in production environments. These case sealing systems are adjustable for box size but are best suited to batches of one size. Used in many industries uniform case sealers are a fast and efficient way to speed up many packaging bottle necks.

Case Capacity

	Minimum	Maximum
Length	114mm	Infinite
Width	114mm	559mm
Height	64mm	610mm

Note: Certain length / width / height combinations may not process due to unstable conveying conditions.

Specifications:

Power: 240 Volts, single phase

Operating Speed: 24.4m/min belt speed

Weight: 104kg (uncrated)

Closure Material: 50mm pressure sensitive tape

Options: 75mm tape, conveyor, castors, top squeezers, ink jet printer, 3 phase electrics.

The state of the art top and bottom case taper for sealing boxes effortlessly from 64mm to 610mm in height. A folder/mailer option is also available. This unit incorporates a sealed drive and internally mounted electrical systems.

- Low Maintenance
- CE Approved
- Quick Changeover
- Safe Single Mast
- Heavy Duty
- Simple Adjustments
- Interchangeable Cartridges
- Larger box (option)

Replace:

- Expensive Labour
- Hand Taping
- Unsafe or Old Machines

**LOOKING AT CASE SEALING?
HAVE YOU CONSIDERED CASE CODING
OR PALLET WRAPPING?**

LOVESHAW Europe

A Division of ITW Ltd.

Unit 9 Brunel Gate
West Portway Industrial Estate
Andover, Hampshire England SP10 3SL
Tel:(01264) 357511 Fax:(01264) 355964



Distributor Information:

