



# MC40 MOBILE COMPUTER

## COOL CONSUMER-STYLING ON THE OUTSIDE ' PURE INDUSTRIAL DESIGN ON THE INSIDE

With this sleek pocketable device, everything your associates need to serve your customers is always right at their fingertips. They can scan an item bar code to look up price, inventory availability or item location; look up a gift registry and product information; present a comparison of multiple products; call virtually anyone in the store carrying any type of mobile device for help with a question; ring up the sale and even complete a loyalty card application ' all without ever walking away from the customer. When associates are not assisting customers, the Zebra MC40 can be used to execute the many tasks required to keep your store at its best for your customers, such as price audits, markups and markdowns, replenishing store shelves and line busting. And while the MC40 offers the cool consumer look you want for your customers on the outside, you get the durability, data security and centralized management needed to achieve a true enterprise-class lifecycle ' and low total cost of ownership.

### Real business-class durability

You get the durability that Zebra is famous for ' the MC40 simply works, even if your employees drop it, bump it, use it in a dusty backroom or splash liquid on it.

### Our most advanced scan technology

Associates can scan 1-D and 2-D bar codes printed on paper or displayed on the screen of a customer's mobile phone with laser-style speed ' even if the codes are dirty, damaged or poorly printed. Omni-directional scanning delivers point-and-shoot simplicity ' no need to align the device and bar code.

### Comprehensive and secure payment processing

- Price checks
- Inventory checks
- Item locator
- Price changes/ price audits
- Mobile POS
- Light duty inventory/ stock replenishment
- Line busting
- Assisted selling
- Product comparison
- Electronic coupons ( mobile phone displays)
- Market research
- Store inventory transfers
- Bridal registry lookup
- Financial/loyalty applications
- Planogram management
- Promotion compliance
- Merchandising
- Secret/competitive shopping
- Click and mortar/catalogue orders
- Manager/workforce management
- Training

The integrated magnetic stripe reader allows associates to scan a credit, gift or loyalty card. And with an encrypted head, information is never visible in the clear, helping meet PCI regulations.

**Rich photographic intelligence**

The high-resolution 8 MP camera allows associates to easily document the condition of an incoming shipment, a planogram, promotion compliance and more with the quick press of a button.

**A large 4.3 inch touch-only display**

Provides the screen real-estate to support information-intensive apps, such as product comparisons.

**A powerful voice connection to nearly any other mobile device in your store**

With our unique integrated voice solutions, the MC40 is push-to-talk (PTT) ready right out of the box, easily connecting to other PTT-enabled Zebra mobile computers as well as two-way radios.<sup>1</sup>

**User replaceable battery for guaranteed availability all shift, every shift**

Up to 8 to 10 hours of operation on a single charge virtually eliminates downtime due to a dead battery during a shift; user-swappable batteries protect device uptime and increase device utilization.

**Powerful application performance**

An 800 MHz processor, 8GB Flash memory and support for 802.11a/b/g/n/r WLANs provides desktop-like speed for demanding applications.

**Android fortified for the enterprise**

Extensions (Mx) from Zebra adds new features that transform Android from a consumer operating system (OS) to a true enterprise-class OS.

**Customize with your brand**

Pick the color for the bezel and add your logo to promote your brand. Enables customers to instantly identify your associates and discourages device theft.

**THE MC40 ' THE NEW FACE OF RETAIL MOBILITY.**

For more information, visit [www.zebra.com/mc40](http://www.zebra.com/mc40) or access our global contact directory at [www.zebra.com/contact](http://www.zebra.com/contact)

## SPECIFICATIONS CHART

| PHYSICAL CHARACTERISTICS    |                                                                                                                                                                                                                                    | DATA CAPTURE                                                                                                                                                                  |                                                                                                                                                                                                                                                                                                                                                |
|-----------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Dimensions                  | With Magnetic Stripe Reader (MSR):<br>5.66 in. H x 2.87 in. W x 1.25 in. D<br>143.9 mm H x 72.8 mm W x 31.8 mm D<br>Without Magnetic Stripe Reader:<br>5.66 in. H x 2.87 in. W x 0.79 in. D<br>143.91 mm H x 72.8 mm W x 20.1 mm D | Imager                                                                                                                                                                        | SE4500-DL                                                                                                                                                                                                                                                                                                                                      |
| Weight with Battery         | With MSR: 9.38 oz./266.1 g<br>Without MSR: 9.09 oz./257.7 g                                                                                                                                                                        | Camera                                                                                                                                                                        | Rear-facing 8 MP auto-focus with aiming for bar code scanning and image capture.                                                                                                                                                                                                                                                               |
| Display                     | 4.3 in. capacitive; 480 x 800; 300 NIT                                                                                                                                                                                             | Payment Transactions                                                                                                                                                          | Integrated Magnetic Stripe Reader (MSR) with encrypted head (optional)                                                                                                                                                                                                                                                                         |
| Touchpanel                  | Capacitive dual-touch                                                                                                                                                                                                              | Data Types                                                                                                                                                                    | 1-D/2-D bar codes, photographs, video, signatures, documents; scans credit, loyalty and gift cards as part of a payment transaction (MSR model only)                                                                                                                                                                                           |
| Backlight                   | LED backlight                                                                                                                                                                                                                      | <b>COMMUNICATION AND MESSAGING</b>                                                                                                                                            |                                                                                                                                                                                                                                                                                                                                                |
| Power                       |  PowerPrecision 2680 mAh Li-Ion rechargeable battery                                                                                             |  Workforce Connect Voice Client Certified<br>Workforce Connect PTT Express Client (included) |                                                                                                                                                                                                                                                                                                                                                |
| Backup Battery <sup>2</sup> | NiMH battery (rechargeable) 15 mAh 3.6 V (not user accessible)                                                                                                                                                                     | <b>WIRELESS LAN</b>                                                                                                                                                           |                                                                                                                                                                                                                                                                                                                                                |
| Connectivity                | USB 2.0 OTG connector                                                                                                                                                                                                              | Radio                                                                                                                                                                         | Tri-mode IEEE® 802.11a/b/g/n/r                                                                                                                                                                                                                                                                                                                 |
| Notification                | LED, audio and vibration                                                                                                                                                                                                           | Security                                                                                                                                                                      | <i>Security Modes:</i> Legacy, WPA and WPA2<br><i>Encryption:</i> WEP (40 and 128 bit), TKIP and AES<br><i>Authentication:</i> TLS, TTLS (MS-CHAP), TTLS (MS-CHAP v2), TTLS (PAP), PEAP (MS-CHAP v2), PEAP (GTC), FAST (MS-CHAP v2), FAST (GTC), LEAP.<br><i>Data in Motion:</i> FIPS 140-2 Level 1<br><i>Data at Rest:</i> FIPS 140-2 Level 1 |
| Keypad                      | On-screen keypad                                                                                                                                                                                                                   | Data Rates                                                                                                                                                                    | 802.11b: 1, 2, 5.5, 11 Mbps<br>802.11a/g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps<br>802.11n: 6.5, 13, 19.5, 26, 39, 52, 58.5, 65 Mbps<br>802.11n with SGI: 7.2, 14.4, 21.7, 28.9, 43.3, 57.8, 65, 72.2 Mbps                                                                                                                                         |
| Disinfectant Ready          | Yes (Healthcare version)                                                                                                                                                                                                           | Fast Roam                                                                                                                                                                     | Pre-Authentication, PMKID Caching, Opportunistic Key                                                                                                                                                                                                                                                                                           |
| Colors                      | Silver, Healthcare Blue and White                                                                                                                                                                                                  | <b>PERFORMANCE CHARACTERISTICS</b>                                                                                                                                            |                                                                                                                                                                                                                                                                                                                                                |
| CPU                         | 800MHz OMAP 4 dual-core processor                                                                                                                                                                                                  | <b>USER ENVIRONMENT</b>                                                                                                                                                       |                                                                                                                                                                                                                                                                                                                                                |
| Operating System            | Android 4.1.1                                                                                                                                                                                                                      | Operating Temp.                                                                                                                                                               | 0° C to 50° C / 32° F to 122° F                                                                                                                                                                                                                                                                                                                |
| Memory                      | 1 GB RAM/8 GB Flash                                                                                                                                                                                                                | Storage Temp.                                                                                                                                                                 | -40° C to 70° C / -40° F to 158° F                                                                                                                                                                                                                                                                                                             |

|                                 |                                                                                        |                               |                                                                                                                                                                      |
|---------------------------------|----------------------------------------------------------------------------------------|-------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Humidity</b>                 | 5% to 85% RH<br>non-condensing                                                         |                               | Caching (OKC), Cisco<br>CCKM, Zebra HFSR,<br>802.11r                                                                                                                 |
| <b>Drop<br/>Specification</b>   | Multiple 4 ft./1.2 m drops per<br>MIL-STD 810G; multiple 3 ft./<br>0.9 m drops to tile | <b>Certifications</b>         | Wi-Fi, CCXv4                                                                                                                                                         |
| <b>Tumble<br/>Specification</b> | 500 1.6 ft/0.5 m tumbles;<br>meets and exceeds IEC<br>tumble specifications            | <b>Operating<br/>Channels</b> | Chan 36-165 (5180 ' 5825<br>MHz), Chan 1-13 (2412 -<br>2472 MHz); actual operating<br>channels/frequencies<br>depend on regulatory rules<br>and certification agency |
| <b>Sealing</b>                  | IP54                                                                                   |                               |                                                                                                                                                                      |
| <b>ESD</b>                      | ± 15kVdc air discharge, ±<br>8kVdc direct discharge, ±<br>2kVdc indirect discharge     |                               |                                                                                                                                                                      |

## INTERACTIVE SENSOR TECHNOLOGY (IST)

|                         |                                                                                                           |
|-------------------------|-----------------------------------------------------------------------------------------------------------|
| <b>Motion Sensor</b>    | 3-axis accelerometer<br>provides motion-sensing for<br>dynamic screen orientation<br>and power management |
| <b>Light Sensor</b>     | Automatically adjusts display<br>backlight brightness                                                     |
| <b>Proximity Sensor</b> | Prevents unwanted key<br>presses in handset mode                                                          |

## AUDIO

High-quality speakerphone, wireless (Bluetooth)  
) headset support, PTT headset support,  
handset/speakerphone modes

## WIRELESS PAN

Bluetooth Class II, v 2.1 with EDR; integrated  
antenna

## PERIPHERALS AND ACCESSORIES

Accessories include single and 5-slot charging  
cradles; single and 4-slot battery chargers;  
holster and a wearable carrying solution. BT  
connectivity to RS507 Ring Scanner.  
(Visit [www.zebra.com/mc40](http://www.zebra.com/mc40) for a complete list  
of accessories.)

## REGULATORY

Visit [www.zebra.com/mc40](http://www.zebra.com/mc40) for regulatory  
information

## WARRANTY

Subject to the terms of Zebra's hardware  
warranty statement, the MC40 is warranted  
against defects in workmanship and materials  
for a period of 1 (one) year from the date of  
shipment. For complete warranty statement, go  
to: <http://www.zebra.com/warranty>

## RECOMMENDED SERVICES

Managed Device Service  
Service from the Start with Comprehensive  
Coverage

1. Zebra devices require the complimentary  
Push-to-Talk Express client from Zebra; third  
party mobile devices require Zebra's Unified  
Retail Communications client; two-way radios  
require Zebra's Radio Link server.
2. Refer to the User Manual for charging  
recommendation.
3. Voice client supported in North America



**ZEBRA**

Part number: SS-MC40. Printed in USA 04/15.©2015 ZIH Corp. ZEBRA, the Zebra head graphic and Zebra Technologies logo are trademarks of ZIH Corp, registered in many jurisdictions worldwide. All rights reserved. All other trademarks are the property of their respective owners.

---

**ZEBRA TECHNOLOGIES**