## **TCxWave**

Today's retailers understand that sustainable success depends on delivering a consistent and differentiated brand experience throughout the customer journey. Nowhere is this more important than the place where the majority of transactions are still carried out: the store.

Retailers need point of sale (POS) technology that can support the versatility, style and functionality that a modern store environment demands. That can adapt easily to the changing demands of customers. That can bring new impact to the customer experience. And that can give timely, consistent service to consumers and associates throughout the shopping journey.

TCxWave by Toshiba is a new breed of retail system created to give retailers the freedom to use one platform for multiple purposes throughout the store. TCxWave has the flexibility, performance and distinctive design that global retailers have come to trust from the team that continues to produce the Number 1 store solutions in the industry.

## Giving point-of-sale a place of pride

TCxWave by Toshiba delivers a unique and engaging experience for associates and customers that puts it in a class of its own. Fully functional as a point-ofsale, kiosk or self-service unit, the TCxWave can be positioned in the most logical and advantageous locations without fear of compromising the in-store experience. Developed by award-winning industrial designers, its striking appearance means retailers need no longer hide the POS away in the back of the store but can sit it proudly where it's needed most. Indeed the sleek design of TCxWave means it can play a central role in delivering a consistent and positive brand image and experience throughout the whole store.

# TO GETHER COMMERCE

## Highlights


- Attractive design complements the brand experience
- Screen size choices, including standard and wider screen options, bring new interaction opportunities
- Versatile configuration enables a seamless brand look and customer experience
- Intuitive, quick-to-learn touch technology maximizes associate productivity
- Retail-hardened design and robustness delivers reliability in mission-critical store environments





#### **Distinctive design**

- TCxWave by Toshiba's stylish design is based on a distinctive profile that reflects the "thin is in" style of modern consumer electronics: TCxWave is our slimmest POS or kiosk ever.
- The multi-touch, gesture-based screen is as easy and familiar to use as a smartphone.
- The widescreen format—the widest format on the market means associates and customers can see more and do more.



• Human factor features include right/left-hand card-swiping and maximum flexibility in possible viewing angles and heights.

#### **Unmatched versatility**

- TCxWave can be deployed as a POS, self-service or kiosk.
- Its versatility protects the investment of retailers whose store environment may evolve over time.
- TCxWave by Toshiba's unique design and functionality fit virtually every store setting.

#### **Reliable and robust**

- TCxWave features the kind of retail-hardened design and durability you would expect from the world leader in in-store technology.
- Antiglare screen protection means top performance even in the most demanding environments.
- Solid-state drive options ensure dependable performance at the crucial point of transaction.





Countertop configuration with optional stand.



Kiosk configuration landscape viewing



Kiosk configuration portrait viewing



Multiple viewing angles and heights



Optional MSR and/or customer display

## **Specifications**

| TCxWave Technical<br>Specifications | 6140-A30, A3R, E30, E3R  | 6140-100,10D, E10,<br>E1D, EP1  | 6140-120, 12D, E2O,<br>E2D, EP2  |  |  |  |
|-------------------------------------|--|---|--|--|--|--|
| Processor (clock speed, cache)      | Intel Celeron Quad Core J1900<br>(2 GHz, 2M)   | Intel Celeron 847e<br>(1.10 GHz, 2M)  | Intel Core i3-3217UE<br>(3M Cache, 1.60 GHz)   |  |  |  |
| Chipset                             | Intel J1900  | Intel HM65PCH   | Intel HM65PCH  |  |  |  |
| BIOS                                | AMI  | AMI   | AMI  |  |  |  |
| Memory*,†                           | DDR3 1333 MHz 2 GB Standard<br>8 GB Max  | DDR3 1066 MHz 2 GB<br>Standard 8 GB Max   | DDR3 1066 MHz 2 GB<br>Standard 8 GB Max  |  |  |  |
| Video                               | Intel Integrated Graphics<br>(DisplayPort output)  | Intel Integrated Graphics<br>Device (DisplayPort output)  |  |  |  |  |
| Touch                               | Projected Capacitive Touch Technology<br>5 point multi-touch   | Projected Capacitive TouchProjected Capacitive TouchTechnology 5 point multi-touch*Technology 5 point multi-t(Hardware Support Statement)(Hardware Support Statement)   |  |  |  |  |
| Screen                              | 15 in 4:3, LED back-lit LCD  | 18.5 in. 16:9 LED back-lit LCD 18.5 in. 16:9 LED back-lit L   |  |  |  |  |
| Audio                               | Optional Speaker kit   | Internal PC beeper <sup>‡</sup> Internal PC beeper <sup>‡</sup>   |  |  |  |  |
| Storage                             | Up to 2x Solid State Drives, available<br>in 64 GB or 128 GB   | (1) Solid State Drive, available<br>in 64 GB or 128 GB option   | (1) Solid State Drive, available<br>in 64 GB or 128 GB option  |  |  |  |
| Ethernet                            | 10/100/1000 MB   | 10/100/1000 MB 10/100/1000 MB   |  |  |  |  |
| I/O Ports on Head                   | <ul> <li>(3) USB 2.0,(1) USB 3.0,</li> <li>(2x) RJ45 RS232*, (1) DisplayPort,</li> <li>(1) 10/100/1000 Ethernet, Side</li> <li>access ports: (1) Audio Jack, (1) USB 2.0</li> <li>*BIOS can configure RS232 as powered</li> <li>or standard</li> </ul> | (3) PC USB 2.0, (1) 10/100/1000 Ethernet,<br>(1) DisplayPort, Side access port: (1) PC USB 2.0  |  |  |  |  |
| I/O Ports on Dockable Base          | (1) 24 V Powered USB 2.0, (3) 12 V Powered USB 2.0, (3) PC USB 2.0, (1) 10/100/1000 Ethernet,<br>(1) DisplayPort   |   |  |  |  |  |
| I/O Ports on optional POS Hub       | 1) 24 V Powered USB 2.0, (1) 24 V Cash Drawer Port, (4) 12 V Powered USB 2.0   |   |  |  |  |  |
| Optional integrated I/O             | iButton (plugs into side USB access)<br>2x20*, MSR*,<br>* Additional USB 2.0 port included on<br>module if one or both of these options<br>selected  | 2x2O*, MSR*<br>*Additional USB 2.0 port included on module if one or both of<br>these options selected  |  |  |  |  |
| Trusted Platform Module (TPM)       | No   | This system contains a TPM module. The function of the module<br>is only for safe storage of the data that is needed for authentica-<br>tion and protection against unauthorized access. Algorithms<br>are, AES, symmetric, key length 128 bit, and RSA,<br>key length 512-2048 bit |  |  |  |  |
| Supported Operating Systems         | Windows Embedded POSReady 7*<br>Windows Embedded 8.1 Industry Pro Retail<br>Windows 7 Professional*<br>Window 8.1 Professional<br>SUSE Linux Enterprise Point of Service 12<br>64-bit only except where* is noted,<br>32-bit also supported            | Windows 7 (64-bit and 32-bit), POSReady 7, POSReady 2009,<br>4690 Version 6.4 Enhanced<br>Windows Embedded 8.1 Industry 64-bit<br>Windows Embedded 8.1 Pro 64-bit<br>Windows 8.1 Pro 64-bit   |  |  |  |  |
| Preloads                            | Microsoft preloaded on E3O, E3R<br>Choice of POSReady 7,<br>Windows 7 *64-bit is standard  | Microsoft preloaded on<br>E10, E1D, EP1<br>Choice of POSReady 2009,<br>PORReady7, or Windows 7  | Microsoft preloaded on<br>E2O, E2D, EP2<br>Choice of PORSReady 2009,<br>POSReady 7, or Windows 7                             |  |  |  |
| Warranty                            | A3O and E3O models provide<br>1 year Depot warranty<br>A3R and E3R models provide<br>1 year On Site Repair Warranty  | 10D and E1D models<br>provide 1 year Depot warranty<br>100, E10, and EP1 models<br>provide 1 year On Site<br>Repair Warranty  | 12D and E2D models provide<br>1 year Depot Warranty<br>12O, E2O, and EP2 models<br>provide 1 year On Site Repair<br>warranty |  |  |  |

| Models                  | TCxWave Dimensions                   | Height   | Width              | Depth              | Weight           |
|-------------------------|--------------------------------------|--|--------------------|--------------------|------------------|
| АЗх, ЕЗх                | POS System (head mounted on base)    | 332.6 mm (13.10 in.)   | 367 mm (14.4 in.)  | 305 mm (12 in.)    | 9 kg (20 lbs)    |
|                         | Head                                 | 337 mm (13.25 in.)   | 367 mm (14.4 in.)  | 76 mm (3 in.)      | 5 kg (11 lbs)    |
|                         | Dockable POS Base                    | 191 mm (7.5 in.)   | 367 mm (14.4 in.)  | 292 mm (11.5 in.)  | 4 kg (9 lbs)     |
| 10x, E1x, 12x, E2x, EP2 | POS System (head<br>mounted on base) | Head rotated fully forward<br>336.7mm (13.26 in.)<br>Head rotated fully back<br>332.6 mm (13.10 in.) | 470 mm (18.5 in.)  | 305 mm (12 in.)    | 10.4 kg (23 lbs) |
|                         | Head                                 | 337 mm (13.25 in.)   | 470 mm (18.5 in.)  | 76 mm (3 in.)      | 6.4 kg (14 lbs)  |
|                         | Dockable POS Base                    | 191 mm (7.5 in.)   | 470 mm (18.5 in.)  | 292 mm (11.5 in.)  | 4 kg (9 lbs)     |
| All                     | POS Hub                              | 78 mm (3.073 in.)  | 185 mm (7.289 in.) | 205 mm (8.077 in.) | 2.72 kg (6 lbs)  |

## Why Toshiba?

As the world's leading provider of integrated in-store solutions and retail insights, Toshiba Global Commerce Solutions delivers end-to-end solutions for checkout, consumer interactions and retail operations that unlock amazing new possibilities for our clients and shoppers everywhere. In partnership with the Together Commerce Alliance, our global business partner program, we help bring innovation and value to every retailing experience so that you can delight your customers every day, everywhere.

#### **Together Commerce**

TCxWave is a key focus for Toshiba's Together Commerce vision. Together Commerce brings together every possible pathway of the retail journey, enabling customers to engage with retailers on their own terms. This fundamental shift eliminates the need to control every customer action, favoring instead a collaborative approach in which retailers and customers create mutually rewarding commerce—together.

## For more information

To see how TCxWave can transform your stores and give point-of-sale new pride of place, please visit: toshibacommerce.com

Additionally, Toshiba Global Commerce Solutions can help credit-qualified clients acquire the IT solutions that your business needs in the most cost-effective and strategic way possible through our global financing partner.

### References

- $^{\ast}\,$  MHz/GHz only measures microprocessor internal clock speed; many factors affect applications performance
- † MB/GB equals one million/billion bytes when referring to storage capacity; accessibility may be less
- ‡ USB attached speaker needed external for audio. Support targeted for Second Half 2014



Copyright © 2014 Toshiba Global Commerce Solutions, Inc.

Toshiba Global Commerce Solutions, Inc. 3039 E Cornwallis Road Research Triangle Park, NC 27709 U.S.A.

Printed in the United States of America All Rights Reserved

Toshiba and the Toshiba logo are trademarks or registered trademarks of Toshiba in the United States, other countries, or both.

The information included in this publication could include technical inaccuracies or typographical errors. All such information is provided "AS IS" without warranties of any kind, express or implied, including but not limited to the implied warranties of merchantability or fitness for a particular purpose.

Not all Toshiba products and services are available in every country. All statements regarding Toshiba's future direction and intent are subject to change or withdrawal without notice, and represent goals and objectives only.

The Toshiba Global Commerce Solutions home page on the Internet can be found at toshibacommerce.com

