



THOR VM3

Thor VM3 to komputer mobilny przeznaczony do pracy w najtrudniejszych warunkach w centrach dystrybucyjnych i zakładach produkcyjnych. Oferuje funkcje zaprojektowane w celu wyeliminowania przestoju i maksymalizacji inwestycji kapitału dla przedsiębiorstwa. Funkcja Smart Dock zapewnia natychmiastowe oszczędności kosztów napraw. Komputer można swobodnie wymontowywać i umieszczać w innym pojeździe.

Honeywell

SPECYFIKACJA TECHNICZNA

Procesor	Dual Core Intel Atom E3826 1.5 GHz
System operacyjny	Microsoft Windows Embedded Compact 7 (WEC 7), Microsoft Windows Embedded Standard 7 (WES 7), Microsoft Windows 7 (Win 7), Microsoft Windows Embedded 8.1 Industry Pro (Win 8)
Pamięć	RAM 4GB DDR3
Komunikacja	WWAN Optional software definable (data only) 4G radio: LTE/UMTS/HSPA+/ GSM/GPRS/EDGE/EV-DO Rev; A/1xRTT with data speeds up to 100Mbps downlink and 50 Mbps uplink WLAN 802.11 a/b/g/n; Wi-Fi™ - certified, CCX certified for data WLAN Security Authentication: Support for a full range of 802.1X (EAP) types, including EAP-TLS, PEAP-MSCHA-Pv2, PEAP-GTC, LEAP, and EAP Fast Encryption Support: Support for Static, pre-shared, and dynamic encryption keys, 40-bit and 128-bit keys, WEP, WPA (TKIP), and WPA2 (AES) Encryption Methods WLAN Antennas Dual internal antennas, dual external remote and direct connect antenna accessories WPAN WEC 7, WES 7, Win 7: Bluetooth® 2.0+EDR standard, internal antenna; Win 8: Bluetooth® 4.0 standard, internal antenna GPS Integrated Assisted GPS (A-GPS) with fast position acquisition and low power consumption. Included with WWAN radio
Oprogramowanie	Data Collection Engine for support of external scanners, Bluetooth wireless technology configuration utilities, Microsoft® Internet Explorer, Microsoft® on-screen keyboard, Configuration Cloning Utility, Screen Blanking, Zoom Zone, Launcher
Oprogramowanie opcjonalne	RFTerm & ETE Terminal Emulators, Enterprise Browser, Remote Mastermind (ReM) device management
Grafika	Intel® HD Graphics Base Freq 533 MHz, Burst Freq 667 MHz, supports two displays
Wyświetlacz	12.1" XGA (1024x768)
Klawiatura	7 wielofunkcyjnych klawiszy
Opcje	zestawy do montażu na wózku widłowym, skanery 1D i 2D, zasilacze awaryjne, zestawy zasilające do montażu na ścianie i inne
Temperatura	Pracy: -20° do +50°C Przechowywania: -20° do 50°C
Waga	3 kg
Wilgotność	5% do 95% wilgotności względnej, bez kondensacji
Parametry fizyczne	318 x 260 x 62 mm

Zapewniamy oprogramowanie i materiały eksploatacyjne renomowanych firm



EXCELLENCE IN:

digital & flexo label printing and converting
automated labelling systems
supply chain management solutions
professional multi-platform services



MEMBER OF

