



◉ **DISPLAY YOUR BUSINESS AT ITS BEST**

From opening to the close of business, robust Toshiba TD-E series displays deliver engaging commercial content and are built to run non-stop for 16 hours per day. The TD-E models are tireless performers, boasting Full HD 1080p resolution and a 178° viewing angle, so your messages always have maximum impact.

Designed for value and flexibility, a wide range of connections and several mounting options are available for a variety of environments. Use the RS-232 port to control the display from a central location and to fine-tune the picture settings. Enhanced functionality can be easily achieved too, thanks to the Open Pluggable Specification (OPS) slot. You'll be set up in no time with a dynamic digital signage solution that was made for meeting your business targets.



Communicate high-quality content on a robust display built to run non-stop for 16 hours per day, 7 days a week.



Thanks to the RS-232 port you can control your display's power and input settings from a central location.



The high brightness screen makes sure your customers always get the full impact of your content.



The Open Pluggable Specification (OPS) slot means complete compatibility with the industry standard specification.



With Full HD 1080p resolution and a wide 178° viewing angle, your messages always have maximum impact.

TECHNICAL SPECIFICATIONS

SCREEN

Diagonal Screen Size	126 cm (50")
Screen Format	16:9
Panel Type	Edge LED
Light Output	500 cd/m ²
Recommended Maximum Usage (Hours)	16
Panel Life (Hours)	30000.0
Backlight	LED
Backlight Scanning	Yes
LED Zones	Edge
Bezel Width	12 mm
Bezel Width Including Non-Active Screen	15mm
Visible Area (H x V)	1095,85 (H) x 616,41 (V)
Panel Resolution	1920 x 1080
Pixel Pitch	0.571 (H) x 0.571 (V)
Display Colours	8-bit, 16,7M colours
Viewing Angle (°)	178
Screen Finish	Anti Glare coating
Native Contrast (number)	1200 : 1
Response Time (ms)	6 ms
Portrait Mode	Yes

OTHER FEATURES

OPS Slot	Yes
Signal Power Off	Yes

INPUTS

HDMI	up to 1920 x 1080 @ 60Hz
HDMI Support Type	HDMI 1.3
Analogue D-SUB	Yes
RS232	Yes
Mini Jack (Audio)	Yes

SUPPORTED INPUT RESOLUTIONS

VGA (D-Sub)	up to 1920 x 1080 @ 60Hz
-------------	--------------------------

CERTIFICATIONS

Safety	Yes
EMC	Yes

OPERATION

Operating Temperature	0 - 50 degree
Operating Humidity	10-90 %
Recommended Maximum Usage (Hours)	16

POWER

Input	AC 220-240 V
Active Consumption	75 W

Standby Consumption	< 0.5 W
Mains Plug Type	EU/UK

DIMENSIONS (APPROX)

Width (mm)	1120
Width Bezel (mm)	12
Height Bottom Deco (mm)	15
Height Without Stand (mm)	645.5
Depth Without Stand (mm) - Minimum Point	28
Depth Without Stand (mm) - Maximum Point	79
Weight Without Stand (kg)	22
VESA - W x H (Screw Type)	400 x 400

ACCESSORIES (INCLUDED IN CARTON BOX)

Remote Control (Type)	Yes CT-8047
Remote Control Battery	Yes
Instruction Manual (QSUG)	Yes
Power Lead	Yes