



Technical Specifications		
	RJ-3050	RJ-3150
Printing Technology	Direct Thermal	
Print Resolution	203 dpi	
Maximum Printing Speed	5 ips (127mm/sec.)	
Dimensions (W x H x D)	4.4" x 3.16" x 7.32" (112mm x 80mm x 186mm)	4.5" x 3.23" x 7.44" (116mm x 82mm x 189mm)
Weight with Battery	1.34 lbs. (610 g.)	1.43 lbs. (680 g.)
User Interface	Large buttons and LEDs	Large color LCD with intuitive, interactive menus
Memory	RAM:32MB / Flash:32MB	
Print Width – Max	2.83" (72mm)	
Roll Width – Max/Min	3.14" (80 mm) / 1.0" (25.4 mm)	
Maximum Roll Diameter	2.6" (66 mm)	
Brother Genuine Media	Receipts, Labels & tags w/black mark	Labels, Tags & Receipts
Sealing Certification	IP54	
Drop Protection	1.2m (4ft.) (Under Brother™ standard environment)	1.8m (6ft.) (Under Brother™ standard environment)
Barcodes	Linear: CODE 39, ITF(I-2/5), EAN-8, EAN-13, 2 or 5 digit extensions, UPC-A, UPC-E, 2 or 5 digit extensions, CODABAR (NW-7), CODE 128, GS1-128 (UCC/EAN 128), CODE93, POSTNET, MSI, GS1 Databar (RSS14, RSS14 Stacked, RSS14 Truncation, RSS14 Stacked Omnidirectional, RSS Limited, RSS Expanded, RSS Expanded Stacked) 2-Dimensional: QR Code (model 1, model 2, micro QR), Maxicode, PDF417 (Standard, Truncate, MicroPDF417), Data Matrix (ECC200 Square, ECC200 Rectangular), Aztec	
OS Support	Windows® XP, Windows Vista®, Windows® 7, Windows® 8, 8.1, Windows® Server 2003, 2008/R2, 2012/R2, SDK's for Android™ 2.2 & higher, iOS® 5 and later, Windows Mobile	
Printer Languages	BPL (P-touch® Template 2.0), Raster, ESC/P	
Emulations	ZPL II®, CPCL	
Software/Utilities	P-touch® Editor 5.0, P-touch® Transfer Manager 2.1, BRAdmin Light, BRAdmin Pro	
Interface	Dual radio – Wi-Fi® (802.11b/g/n) and Bluetooth® technology interfaces	
WLAN Security	AdHoc mode: Open system (None/WEP) Infrastructure mode: Open system (None/WEP64/WEP128), Common key authentication (WEP), WPA/WPA2-PSK (TKIP+AES), LEAP (CKIP), EAP-FAST (TKIP/AES), PEAP (TKIP/AES) *3, EAP-TLS (TKIP/AES), EAP-TTLS (TKIP/AES) Wireless direct mode: WPA2-PSK (AES)	
Resident Fonts	5 BMP: Letter Gothic Bold 8 fonts (9,11,15,18,21,26,28,56dot), Helsinki: 3 fonts (15,21,28dot), Symbol: 1 font (24dot), OCR-A: 1font (21dot), OCR-B: 1font (28dot) & 3 Outline fonts: Letter Gothic Regular, Helsinki, Utah Condensed Bold	
Battery Life	500 charge cycles (50% battery capacity assurance)	
Charging Time	Less than 3 hours	
Media Sensors	Black Mark (Reflective)	Gap/Bar (Transmissive/Reflective)
Operating Temperature	-10°C to +50°C	
USB Host	Not Available	Type A
Options/Accessories*	Shoulder strap, rechargeable interchangeable Li-ion battery, printer charging cradle, battery charger, AC adaptor, DC vehicle adaptor	
Warranty	1-year "bumper-to-bumper" warranty▼	2-year "bumper-to-bumper" warranty▼

ASK US ABOUT OUR ACCESSORIES*

* Requires additional purchase. ▼See limited warranty for details. For warranty information, ask your Brother Mobile Solutions, Inc. sales representative or visit www.brothermobilesolutions.com. RuggedJet™ Specifications subject to change without notice.

Premium Brother" Papers for the RuggedJet" 3 Line

RuggedJet™ models accept a variety of premium Brother™ thermal media

Receipt Paper (3" wide)

- Standard (Uncoated) Receipt Paper
- Premium (Top-coated) Receipt Paper
- Weatherproof (Synthetic) Receipt Paper

Label Rolls (Die-cut media)

- 2.25" x 1.25" Labels 3" x 4" Labels
- 3" x 1.75" Labels 3" x 5" Labels
- 3" x 2" Labels



BROTHER MOBILE SOLUTIONS, INC.

For more information, call 1-800-543-6144, or visit www.brothermobilesolutions.com

