

LITTLE DAVID®

Uniform Legend Case Sealer

The Little David® Uniform Legend Case Sealer is designed to reliably seal uniform runs of boxes. The Uniform Legend uses pressure sensitive tape to seal boxes in the range of 2-1/2" to 24" high. It can also accommodate a folder/mailler option.

These are what make Legends:

- Simple Operation
- Low Maintenance
- Interchangeable Tape Cartridges
- UL Listed
- Quick Changeover
- Heavy Duty
- Reliable
- Safe
- Cost Effective



www.loveshaw.com

Uniform Legend

Safe —

- Patented single mast design allows clear access to all components

Heavy Duty Design —

- 11-gauge steel construction
- Modern design encloses and protects the mast, drive system, side rails, and top head

Top cartridge tips back on head for tape threading.

Quick Change Over —

- Extended side rails center box
- Convenient palm grip knobs allow for easy slide and lock adjustments

Optional Little David MicroJet® adapter allows you to code while you seal.

Flexible —

- Interchangeable CaseLocker® ST top and bottom tape cartridge.

Patented leg extensions are clearly marked with graduated scales in both inches and metric dimensions. Leg adjustments slide and lock in place to accommodate conveyor heights from 22.25 in. to 32.25 in. (565 mm to 819 mm)

Features:

Reliable Performance — Warranty

- 1 Year all components*
- 2 Years Gear Reducer
- 3 Years Cartridge*


*Moving and wear parts are not included. Other restrictions may apply. Consult Loveshaw or your authorized Little David® Distributor for details

Flexible —

- Tapes boxes from 2" (51 mm) to 24" (610 mm)
- Converts from 2" to 3" wide tape

Easy Operation —

- Plug in operation
- Minimal operator training required
- Sealed drive system
- CaseLocker® ST tape cartridge requires no lubrication



Safe —

- UL listed
- Patented single mast design allows clear access
- Knife guard system of the CaseLocker® ST tape cartridge only allows the blade to be exposed when the rollers have been depressed

Options:

- Casters
- Folder/Mailer
- Leg adjustments to accommodate various conveyor heights
- High mast for box heights to 34" (864 mm)
- Front and rear standard or roller pack table

Specifications:

Power Requirements:

115 – 220 volts, single phase, 60 cycle
(other voltage available, consult Loveshaw)

Operating Speed:

Continuous belt drive; 80'/minute (24.4 m/min.)
(production rate depends on box size & operator dexterity)

Weight:

230 lbs (104 kg) uncrated

Case Capacity: (with 2" wide Caselocker® ST Cartridge)

Min: Height 2-1/2" (64 mm), Width 4-1/2" (114 mm), Length 4- 1/2" (114 mm)

Max: Height 24" (610 mm)*, Width 22" (559 mm), Length infinite

*High mast version accommodates box heights to 34" (864 mm)

LOVESHAW **LOVESHAW Europe**
an **ITW** Company A Division of ITW Ltd.

LITTLE DAVID PRODUCTS DIVISION
Route 296 Box 83
South Canaan, PA 18459
(570) 937.4921 Fax (570) 937.3229
1(800) 581-7119

Unit 9 Brunel Gate,
West Portway Industrial Estate
Andover, Hampshire England SP 10 3 SL
Tel: (1264) 357511 Fax: (1264) 355964

visit
www.loveshaw.com

