

# **Bluetooth® Cordless System**

### **Instinctive Reading Intelligent Scanner**









## **General Description**

Gryphon™ BT 100 and BT200 share the same powerful architecture of the other models of the Gryphon™ family, with a special addition: the latest innovation in the wireless communication, Bluetooth® technology. This technology provides the operator with wider mobility and no cable constraint. Bluetooth® is a standard defined worldwide, and it allows various devices manufactured by different companies to easily connect and communicate with each other.

The new Gryphon™ BT contains the Datalogic Bluetooth® radio module, which is compliant with the up-to-date Bluetooth® 1.2 standard. It can communicate with its base receiver or any PC, Laptop, PDA, mobile phone, printer etc. that includes an embedded Bluetooth® module or an external commercial Bluetooth® dongle. The implemented Bluetooth® profile (i.e. the "protocol" used for communication) is provided by the SPP=Serial Port Profile: the Bluetooth® device is seen by the host like a virtual COM port. Moreover, the enclosed software utility has been developed to convert serial input to keyboard emulation, providing more interface possibilities for the user.

Bluetooth<sup>®</sup> technology has been added to a first class scanner. Thanks to the state-of-art optics and a decode rate of 270 scans/sec, reading performance in terms of decoding capability and reading quickness makes the Gryphon<sup>™</sup> BT very user friendly, intuitive and fast.

Furthermore, the "blue spot" produced by the Gryphon $^{\mathsf{TM}}$  BT, provides "good reading" feedback directly on the code and makes the user's job easier, especially in noisy environments.

### **Features**

- Bluetooth® 1.2 compliant (Serial Port Profile)
- Virtual COM and keyboard emulation data input
- > High speed data transmission: zero delay
- > RSS symbologies, PDF417 and linear bar code decoding
- > Package contents:
  - Gryphon™ BT
  - OM Gryphon™ BT receiver or C-Gryphon™ charger
  - CD-ROM Gryphon™ BT
  - Gryphon BT™ Quick Reference
- > Sunrise 2005 compliant

### **Applications**

- "Cable replacement" for POS/In-Store
- > Document Handling
- > Shop Inventory Management

## **Specifications**

#### **BLUETOOTH® RADIO COMMUNICATION**

R&TTE and Bluetooth 1.2 Qualified 802.11b co-existence 2.4 to 2.48 GHz SPP (Serial Port Profile) Bluetooth 1.1 compliant

RADIO FREQUENCY

COMMUNICATION EFFECTIVE RADIATED POWER Up to 4 dBm transmit power for class 2 operation

BIT RATE Up to 921 Kbps

RADIO RANGE 10 m in a typical environment

**ELECTRICAL CHARACTERISTICS** 

Direct plug-in 9-28 VDC (C-Gryphon™ B/C) 2 AA NiMh batteries POWER SUPPLY

BATTERY TYPE RECHARGE TIME 4 hours max.

OPERATING AUTONOMY 24,000 reads - NiMh 8W max. (C-Gryphon™ B/C) POWER CONSUMPTION

MECHANICAL CHARACTERISTICS DIMENSIONS

208 x 107 x 55.5 mm 280 g (Gryphon™ BT with batteries); 250 g (C-Gryphon™ B/C) ABS and Polycarbonate, plus co-moulded rubber WEIGHT CASE MATERIAL

PERFORMANCE

CCD solid state (3648 pixels)

SENSOR
MAX. SCAN RATE
MAX. RESOLUTION
PRINT CONTRAST RATIO (min.) 270 scans/sec 0.076 mm (3 mils)

INTERFACES

Soft Hills's pics=15%
RS232 (C-Gryphon™ B/C)
Skew: ±80°; Pitch: 65°; Tilt: ±35° (EAN13, M=0.8, PCS=0.9)
Good Read Blue LED, "Blue spot" on the code, adjustable tone "beeper" READING ANGLE READING INDICATORS

**ENHANCED FEATURES** 

Good Read Blue LED, "Blue spot" on the code, adjustable tone "beeper" (Gryphon™ BT), Battery Charging (red), Charge completed (green), Power (yellow) (C-Gryphon™ B/C)
Puzzle Solver™, data editing and data concatenation
RSS variants, 2/5 family, Code 39 (plus Code 32, Cip 39), EAN/UPC, ISBN/ISSN, EAN 128, Code 128, ISBT 128, Code 93, Code 11, CODABAR, TELEPEN, PLESSEY, Code MSI, Code Delta IBM, Code 16K, Code 49
PDF 417 BAR CODES

BT200 Model

PROGRAMMING METHOD Manual Reading special bar codes

S/W commands through the serial port Windows configuration program Automatic (with RS232)

Sm@rtSet


#### **ENVIRONMENTAL CHARACTERISTICS**

DROP RESISTANCE IEC68-2-32 TEST ED, resists repeated drops from 1.8m onto a concrete surface


OPERATING TEMPERATURE STORAGE TEMPERATURE 0 to 40° C (32 to 104° F) -20 to 70° C (-4 to 158° F) Up to 100.000 lux 90% non condensing AMBIENT LIGHT CONDITIONS HUMIDITY

ENVIRONMENTAL PROTECTION IP30

## **Reading Diagrams**



Standard reading zone



PDF417 reading zone

## Connectivity



The introduction of Bluetooth® technology offers a wireless cost-effective solution when basic cable-free mobility is required. The Gryphon™ bar code reader can be connected to mobile computers, printers, mobile phones and other Bluetooth® compliant devices. The new Gryphon™ BT provides new application possibilities. A bar code reader can now be used, for example, in mobile shopping applications by simply transmitting data to a Laptop or a PDA. Bluetooth® is a standard communication protocol that provides full connectivity between various devices. It guarantees quick and reliable communication and data transmission.



Product and Company names and logos referenced may be either trademarks or registered trademarks of their respective companies. We reserve the right to make modifications and improvements.

